

INDUSTRIAL
LUBRICATING OILS

INDUSTRIAL
GEAR OILS

INDUSTRIAL
GREASES

FOOD GRADE
LUBRICANTS

SYNTHETIC
LUBRICANTS

SPECIALTY
PRODUCTS

ORELUBE ET-2A Grease

Food Grade Lubricating Grease



The Orelube Corporation

Specialty Industrial Lubricants Since 1958



ET-2A is non-toxic, food grade EP grease manufactured using high purity USP white mineral oil thickened with Aluminum complex soap.

NSF Registered (No. 070012) H1 Aluminum complex EP grease for the lubrication of machinery used to produce, process, package and/or transport food, beverage and pharmaceuticals where incidental contact with product may occur.

All the components in ET-2A are in accordance with FDA regulation 21 CFR 178.3570 – Lubricants with incidental food contact.

- EP and wear protection
- High dropping point
- Superior water resistance
- Mechanical (shear) stability when worked maintains consistency
- Tackifier provides extra-adhesive properties

CONTAINERS ■■■



ET-2A Cartridge
(14.5 oz - 411 g)



ET-2A Pail
(35 Lb - 15.9 Kg)



ET-2A Keg
(120 Lb - 54.4 Kg)



ET-2A Drum 55 Gal
(400 Lb - 181.4 Kg)

TYPICAL PROPERTIES

NLGI Grade	2
Color	White
Operating Temperature Range	-10 to 350 F
Penetration, ASTM D 217	
Worked, 60 strokes	272
Worked, 10,000 strokes	273
Dropping Point, ASTM D 2265, F	550
Base Oil Viscosity, ASTM D 445	
cSt @ 40 C	110
Water Washout, ASTM D 1264	
% wt. loss @ 100 F	0.2
Rust Test, ASTM D 1743	Pass
Oxidation Stability, ASTM D 942	
100 hrs. @ 210 F, psi loss	3
4-Ball EP, ASTM D 2596	
Weld load, kg	315
Load wear index, kg	41
4-Ball Wear, ASTM D 2266	
167 F, 40 kg, 1200 rpm, 1 hr.	
Scar diameter, mm	0.51

CERTIFICATIONS ■■■



Nonfood Compounds
Program Listed H1
NSF registration

APPLICATIONS ■■■



The Orelube Corporation

Specialty Industrial Lubricants Since 1958

The Orelube Corporation
20 Sawgrass Drive
Bellport, NY 11713
USA

Phone: +1 800.645.9124
+1 631.205.9700
Fax: +1 631.205.9797
Website: www.orelube.com



NSF-ISR

Registered
to ISO 9001