

ORELUBE ET-2A Grease

Food Grade Lubricating Grease



The Orelube Corporation

Specialty Industrial Lubricants Since 1958



ET-2A is non-toxic, food grade EP grease manufactured using high purity USP white mineral oil thickened with Aluminum complex soap.

NSF Registered (No. 070012) H1 Aluminum complex grease for the lubrication of machinery used to produce, process, package and/or transport food, beverage and pharmaceuticals where incidental contact with product may occur.

All the components in ET-2A are in accordance with FDA regulation 21 CFR 178.3570 – Lubricants with incidental food contact.

- EP and wear preventive properties
- High dropping point
- Superior water resistance
- Mechanical (shear) stability when worked maintains consistency
- Tackifier provides extra-adhesive properties

CONTAINERS ■■■



ET-2A Cartridge
(14.5 oz - 411 g)



ET-2A Pail
(35 Lb - 15.9 Kg)



ET-2A Keg
(120 Lb - 54.4 Kg)



ET-2A Drum
(400 Lb - 181.4 Kg)

TYPICAL PROPERTIES


NLGI Grade	2
Color	White
Operating Temperature Range	-10 to 350 F
Penetration, ASTM D217	
Worked, 60 strokes	272
Dropping Point, ASTM D2265, F	550
Base Oil Viscosity, ASTM D445	
cSt @ 40 C	110
Water Washout, ASTM D1264	
% wt. loss @ 100 F	0.2
Rust Test, ASTM D1743	Pass
Oxidation Stability, ASTM D942	
100 hrs. @ 210 F, psi loss	3
4-Ball EP, ASTM D2596	
Weld load, kg	315
Load wear index, kg	41
4-Ball Wear, ASTM D2266	
167 F, 40 kg, 1200 rpm, 1 hr.	
Scar diameter, mm	0.51

CERTIFICATIONS ■■■



Nonfood Compounds
Program Listed H1
NSF registration

APPLICATIONS ■■■



The Orelube Corporation

Specialty Industrial Lubricants Since 1958

The Orelube Corporation
20 Sawgrass Drive
Bellport, NY 11713
USA

Phone: +1 800.645.9124
+1 631.205.9700
Fax: +1 631.205.9797
Website: www.orelube.com



NSF-ISR

Registered
to ISO 9001