

ORELUBE ET-Y OILS

Food Grade Lubricating Oils



The Orelube Corporation

Specialty Industrial Lubricants Since 1958



ET-Y Oils are non-toxic, food grade lubricants manufactured using high purity USP white mineral oils.

NSF Registered H1 lubricating oils for the lubrication of machinery used to produce, process, package and/or transport food, beverage and pharmaceuticals where incidental contact with product may occur.

All the components in ET-Y oils are in accordance with FDA regulation 21 CFR 178.3570 – Lubricants with incidental food contact

- Translucent
- Superior wear preventive properties
- Oxidation stability
- Tackifier for extra-adhesive properties

CONTAINERS ■■■



ET-Y Oils Pail
(5 Gal - 18.9 Lt)



ET-Y Oils Keg
(15 Gal - 57 Lt)



ET-Y Oils Drum
(55 Gal - 208 Lt)

CERTIFICATIONS ■■■




TYPICAL PROPERTIES ■■■

ISO VG
NSF Registration No.
Viscosity, ASTM D445
cSt @ 40 C
Pour point, F
Flash point, F COC
Rust test, ASTM D665 A & B
4-Ball Wear, ASTM D4172
1200 rpm, 40 kg, 167 F, 1 hr.
Scar diameter, mm

	ET-5Y	ET-10Y	ET-20Y	ET-30Y	ET-40Y	ET-90Y	ET-320Y	ET-90/140Y	ET-140Y
ISO VG	15	46	68	100	150	220	320	460	680
NSF Registration No.	070019	070010	070016	070017	070018	070021	142184	070020	070011
Viscosity, ASTM D445 cSt @ 40 C	16.3	44.2	66.2	104.2	157	204.4	319.5	441.4	629
Pour point, F	-25	-20	-15	-10	-10	0	0	0	0
Flash point, F COC	>250	>250	>250	>250	>250	>250	>250	>250	>250
Rust test, ASTM D665 A & B	Pass	Pass	Pass						
4-Ball Wear, ASTM D4172 1200 rpm, 40 kg, 167 F, 1 hr. Scar diameter, mm	0.40	0.40	0.40	0.40	0.40	0.40	0.40	0.40	0.40

APPLICATIONS ■■■



The Orelube Corporation

Specialty Industrial Lubricants Since 1958

The Orelube Corporation
20 Sawgrass Drive
Bellport, NY 11713
USA

Phone: +1 800.645.9124
+1 631.205.9700
Fax: +1 631.205.9797
Website: www.orelube.com



NSF-ISR

Registered
to ISO 9001