ORELUBE PRG-FL Grease

Food Grade Open Gear Grease





PRG-FL is non-toxic, food grade grease for open or semi-enclosed gears manufactured using special synthetic polymers and USP white mineral oil thickened with Aluminum complex soap.

NSF Registered (No. 138412) H1 Aluminum complex grease for the lubrication of machinery used to produce, process, package and/or transport food, beverage and pharmaceuticals where incidental contact with product may occur.

All the components in PRG-FL are in accordance with FDA regulation 21 CFR 178.3570 - Lubricants with incidental food contact.

Weld load, kg

- Superior water resistance
- Extra-tacky, adhesive properties
- Tough, tenacious lubricating film
- Adheres to gear teeth on rotating gears
- EP and wear preventive properties
- Operating temperature range 10 to 177 C

CONTAINERS ■■■



PRG-FL Pail (35 Lb - 15.9 Kg)



PRG-FL Keg (120 Lb - 54.4 Kg)



PRG-FL Drum (400 l b - 181 4 Kg)

TYPICAL PROPERTIES

Color Off-white 300 - 320 Unworked penetration, ASTM D217 Dropping point, F (C) > 500 (260) ASTM D2265 Base oil viscosity, ASTM D445 cSt @ 100 F (38 C) 110 Rust Test, ASTM D1743 **Pass** 4-Ball EP, ASTM D2596

CERTIFICATIONS ■■■







APPLICATIONS ■■■



USA



The Orelube Corporation 20 Sawgrass Drive Bellport, NY 11713

Phone: +1 800.645.9124 +1 631.205.9700 +1 631.205.9797 Fax: Website: www.orelube.com



315

Registered

to ISO 9001