ORELUBE SYNCHAIN OILS

Food Grade Synthetic Lubricating Oils





SYNCHAIN Oils are non-toxic, food grade oils manufactured using synthetic PAO fluids.

NSF Registered H1 lubricating oils for the lubrication of machinery used to produce, process, package and/or transport food, beverage and pharmaceuticals where incidental contact with product may occur.

All the components in SYNCHAIN Oils are in accordance with FDA regulation 21 CFR 178.3570 – Lubricants with incidental food contact.

- · Wide operating temperature range
- Superior wear preventive properties
- Food grade oven chain lubrication up to 350 F (177 C) with intermittent use up to 400 F (204 C)

CONTAINERS ■■■



SYNCHAIN Oils Pail (5 Gal - 18.9 Lt)



SYNCHAIN Oils Keg (15 Gal - 57 Lt)



SYNCHAIN Oils Drum (55 Gal - 208 Lt)

TYPICAL PROPERTIES SYNCHAIN 100 SYNCHAIN 220

_			
ISO VG	100	220	460
NSF Registration No.	137823	155611	147842
Viscosity, ASTM D445			
cSt @ 40 C	101.5	228.3	471.3
Flash Point, F (C)	500 (260)	520 (271)	530 (277)
Pour Point, F (C)	-45 (-43)	-44 (-42)	-36 (-38)
4-Ball Wear, ASTM D2266			
167 F. 40 kg. 1200 rpm. 1 hr.			

0.35

0.35

CERTIFICATIONS ■■■







APPLICATIONS ■■■



USA







Scar diameter, mm





The Orelube Corporation 20 Sawgrass Drive Bellport, NY 11713 Phone: +1 800.645.9124 +1 631.205.9700 Fax: +1 631.205.9797 Website: www.orelube.com



SYNCHAIN 460

0.33