

INDUSTRIAL
LUBRICATING OILS

INDUSTRIAL
GEAR OILS

INDUSTRIAL
GREASES

FOOD GRADE
LUBRICANTS

SYNTHETIC
LUBRICANTS

SPECIALTY
PRODUCTS

ORELUBE ET-S Oils

Food Grade Synthetic Lubricating Oils



The Orelube Corporation

Specialty Industrial Lubricants Since 1958



ET-S Oils are non-toxic, food grade synthetic lubricating oils manufactured using synthetic PAO fluids.

NSF Registered H1 lubricating oils for the lubrication of machinery used to produce, process, package and/or transport food, beverage and pharmaceuticals where incidental contact with product may occur.

All the components in ET-S Oils are in accordance with FDA regulation 21 CFR 178.3570 – Lubricants with incidental food contact.

- Wide operating temperature range
- Superior wear preventive properties
- High film strength and lubricity
- Superior low temperature lubrication
- Oxidation stability

CONTAINERS ■■■



ET-S Oils Pail
(5 Gal- 18.9 Lt)



ET-S Oils Keg
(15 Gal - 57 Lt)



ET-S Oils Drum
(55 Gal - 208 Lt)


CERTIFICATIONS ■■■



TYPICAL PROPERTIES ■■■

| | ET-10 S | ET-20 S | ET-30 S | ET-40 S | ET-90 S | ET-140 S |
|---|---------|---------|---------|---------|---------|----------|
| ISO VG | 32 | 68 | 100 | 150 | 220 | 460 |
| NSF Registration No. | 128449 | 127826 | 137000 | 128451 | 128448 | 128452 |
| Viscosity, ASTM D445 cSt @ 40 C | 30.5 | 68.0 | 101.5 | 151.9 | 230.4 | 473.4 |
| Pour point, F | -71 | -40 | -40 | -40 | -40 | -40 |
| Flash point, F COC | > 250 | > 250 | > 250 | > 250 | > 250 | > 250 |
| Rust test, ASTM D665 A & B | Pass | Pass | Pass | Pass | Pass | Pass |
| 4-Ball Wear, ASTM D4172 1200 rpm, 40 kg, 167 F, 1 hr. Scar diameter, mm | 0.40 | 0.40 | 0.40 | 0.40 | 0.40 | 0.40 |

APPLICATIONS ■■■



The Orelube Corporation

Specialty Industrial Lubricants Since 1958

The Orelube Corporation
20 Sawgrass Drive
Bellport, NY 11713
USA

Phone: +1 631.205.9700
Fax: +1 631.205.9797
Website: www.orelube.com



NSF-ISR

Registered
to ISO 9001